

◆ Connection Cable

8P-T3

Type	8P-T, double-shielded
Connectors	2 x male, 1 x female
Length	1.5m+1.2m



◆ Interpreter Cable

25PS-03/05/10

DB-25 double shielded cable	
Moulded male/female connector, long screws	
Length	3m/5m/10m



◆ Serial cable

RS-232

Db9 connector, 2 x female	
Length	5 metres



◆ Storage Case

GX-48

Type	Aluminum carrycase
Positions	48
Dimensions	500×330×200 mm(W×D×H)



◆ Tripod stand

GX-315

Type	Floor standing
Height	600-1500mm
Angle	horizontal



All rights reserved. The information and specifications included are subject to change without prior notice.

GONSIN CONFERENCE EQUIPMENT CO.,LTD.
www.gonsin.com



GONSIN®



Accessories

◆ Charging Case

GX-60

◆ Features

- ◆ Aluminum storage flight case for charging & storage
- ◆ Microprocessor-based smart charging circuit
- ◆ Accommodates up to 60 receivers
- ◆ Independent LED indicators for charging status
- ◆ Less than 2.5 hours are needed to fully charge 60 units
- ◆ Fully charged units can remain in the case
- ◆ 2 butterfly locks, wheels and 3 handles, easy to carry



◆ Technical Specifications

Power input	AC 100-240V, 50-60Hz, 240W
Power output	5V, 20A
Charging status indicator	Charging (red light) fully charged (green light)
Operating temperature	0-45°C
Storage temperature	-20-50°C
Dimensions	686×433×235mm (W x D x H)
Net Weight	14.5 Kg
Net weight with 60 receivers	21.7kg

◆ Charging Case

GX-20/20S

◆ Features

- ◆ Handy aluminium/plastic case for charging & storage
- ◆ Microprocessor-based smart charging circuit
- ◆ Accommodates up to 20 receivers or voting units
- ◆ Microprocessor-based smart charging circuit
- ◆ Independent LED indicators for charging status
- ◆ About 4 hours are needed to fully charged 20 units
- ◆ Receivers can be left in the case after complete charge
- ◆ AC/DC adapter with power cord



◆ Technical Specifications

Power input	100-240V, 50-60Hz
Power output	7.5V, 8A
Operating temperature	0-45°C
Storage temperature	-20-50°C
Dimensions	590x300x200 mm (W x D x H)
Net Weight	6.65 Kg

◆ Interpreter Headset

TC-D2

Closed-ear stereo headset with mic and vol control

Connectors	3.5mm stereo plugs
Impedance	60Ω±15%
Frequency response	20Hz to 20KHz
Microphone type	Omni-directional dynamic
Microphone sensitivity (1kHz)	-58±2dB
Cord length	2 meters



◆ Stereo Headphone

TC-D3

Adjustable headband & soft foam ear pads

40mm drivers for dynamic stereo sound	
120cm single entry cord with 3.5mm plug	
Ergonomic design	
Super heavy bass	
Frequency response	20 Hz - 20 kHz
Impedance	32 ohms ±15%
Sensitivity	94dB ±3dB
Maximum power input	30mW



◆ IC Card Encoder

GX-870(IC)

Chip card reader/writer

Encodes delegate ID cards

Interface type USB

Speed <0.2 sec



◆ IC Card

BL7442

Every card has an unique 32-bit serial number

Different password can be preset via software

Rewrite time >100,000 times

Life time >10 years

Material PVC

Operating temperature -20°C to 85°C

Dimensions 85.6x53.98x0.8 (LxWxD)



◆ Extension Cable

13PS-03/05/10/15/20

Type 13PS, double-shielded

Connector 1 x male, 1 x female

Length 3/5/10/15/20 metres



◆ Extension Cable

8PS-03/05/10/15/20

Type 8PS, double-shielded

Connector 1 x male, 1 x female

Length 3/5/10/15/20 metres



◆ Connection Cable

13P-T3

Type 13P-T, double-shielded

Connectors 2 x male, 1 x female

Length 1.5m+1.2m

